

## **DECLARATION OF PERFORMANCE (DOP)**

No. 338201

## Product Type Aerogel High Performance Insulating Plaster

Identification of the product

Fixit 222

Intended use

## Mineral high performance insulating plaster for indoor and outdoor applications

Manufacturer

## FIXIT AG - Im Schachen 416, CH-5113 Holderbank (AG)

Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2 s-1 d-0	EN 998-1: 2010
Capilar water absorption	W 1	
Coefficient of water vapour diffusion ( $\mu$ )	≤ 5	
Thermal conductivity $\lambda_{D}$	0,028 W/mK	
Thermal conductivity group	T 1	
Tensile adhesion strength	NPD	
Durability	NPD	
Dangerous substances	NPD	
Compressive streght	CSI	
Oven-dry density	$\leq$ 220 kg/m <sup>3</sup>	

The performance of the product identified in this statement is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer named in the declaration.

Signed for and on behalf of the manufacturer by:

Management: Philipp h	Hugentobler Reto Galliard		
Management: Philipp Hugentobler, Reto Galliard (Name and function)			
Holderbank, 2014-01-01	This document was produced electron- ically and is valid without signature.		
(Place and date of issue)	(Signature)		